

GRP ENCLOSURES



Available in single, double, and walk-in unit options, each enclosure features a high-quality, robust GRP composite build with a white resin interior finish, sealed against dust and water. Thermal insulation and ventilation come as standard to protect sensitive equipment and maintain optimal internal conditions.



Durability



Security



Weather Protection



Ventilation

SPECIFICATION

- Single door, Double door, and Walk-in unit options
- Available in Green (14-C-39) or Grey (10-A-07) finishes
- White resin interior finish
- Tough GRP composite build resists corrosion, weather, and impact
- Secure hasp and staple locking
- Stainless steel hinges ensure long-lasting, rust-free performance
- Standard Wall construction has been designed and tested to BS476 Part 22 and exceeded a half hour fire rating
- Fire retardant resin is used internally to provide self-extinguishing laminates to BS476 Part 7 Class 2 (Surface spread of flames)
- Sealed against dust, water, and impact for all-weather reliability
- Built-in thermal insulation protects sensitive internal equipment
- Optional ventilation ensures airflow and prevents overheating
- 100mm flange base bolts securely to concrete for a stable install
- IP53 as standard. IP63 achieved when fitted with 3-point locking

Single Door Cabinets				
Order Code	Description	Width(mm)	Depth(mm)	Height(mm)
SP01866	GRP3 – SD – HS Lock – x1 Vent (Green 14C39)	670	380	940
SP01867	GRP4 – SD – HS Lock – x1 Vent (Green 14C39)	750	400	1100
SP01868	GRP5 – SD – HS Lock – x1 Vent (Green 14C39)	925	360	1150
SP01869	GRP6A – SD – HS Lock – x1 Vent (Green 14C39)	935	600	1160
Double Door Cabinets				
SP01870	GRP6 – DD – HS Lock – x1 Vent (Green 14C39)	1065	455	1270
SP01871	GRP7 – DD – HS Lock – x1 Vent (Green 14C39)	1065	650	1270
SP01872	GRP8 – DD – HS Lock – x1 Vent (Green 14C39)	1300	400	1250
SP01873	GRP9 – DD – HS Lock – x1 Vent (Green 14C39)	1400	660	1515
SP01874	GRP10 – DD – HS Lock – x1 Vent (Green 14C39)	1700	800	1600
SP01875	GRP11 – DD – HS Lock – x1 Vent (Green 14C39)	2020	500	1585
SP01876	GRP12 – DD – HS Lock – x1 Vent (Green 14C39)	2020	800	1585
SP01877	GRP12A – DD – HS Lock – x1 Vent (Green 14C39)	1200	1000	2000
Walk-in Double Door Cabinets				
SP01878	GRP13 – WI – HS Lock – x1 Vent (Green 14C39)	2000	500	2000
SP01879	GRP14 – WI – HS Lock – x1 Vent (Green 14C39)	2000	1000	2000
SP01880	GRP15 – WI – HS Lock – x1 Vent (Green 14C39)	2000	1500	2000
SP01881	GRP16 – WI – HS Lock – x1 Vent (Green 14C39)	2000	2000	2000
Walk-in Double Door Cabinets (12mm Plywood Core)				
SP01882	GRP17 – WI – HS Lock – x1 Vent (Green 14C39)	2000	500	2000
SP01883	GRP18 – WI – HS Lock – x1 Vent (Green 14C39)	2000	1000	2000
SP01884	GRP19 – WI – HS Lock – x1 Vent (Green 14C39)	2000	1500	2000
SP01885	GRP20 – WI – HS Lock – x1 Vent (Green 14C39)	2000	2000	2000

Optional Extras
Ventilation & Access
300mm x 300mm Aluminium Louvre Vent
300mm x 225mm Aluminium Louvre Vent
225mm x 225mm Aluminium Louvre Vent
225mm x 150mm Aluminium Louvre Vent
200mm x 100mm Slim Line Hit and Miss Vent
300mm x 150mm Slim Line Hit and Miss Vent

Optional Extras
Lockable Access Flap (Cat-Flap)
300mm x 300mm Lockable Access Flap
Door Stays
90° Stainless Steel Hold Open Door Stay
Locking
3-Point Locking (Padlockable)
High-Low Lockable Clamp Latches

*All GRP Pillars are supplied with a single vent as standard. For enhanced air circulation, we recommend the inclusion of a second vent. Should you wish to add a second vent, please select from the optional extras above.